

Specifications

Type of motor	Powered Winch	Signal Winch
Dimensions	250mm x 193mm x 456mm	250mm x 193mm x 456mm
Weight	12kg / 26.46lbs	11.5kg / 25.35lbs
Power Consumption Max / Average	300W / 150W	200W / 100W
BTU Max / Average	1025 / 475	685 / 315
Power supply	100-240Vac; 50Hz – 60Hz	100-240Vac; 50Hz – 60Hz
Output voltage AC/DC	100-240Vac; 50Hz – 60Hz /36Vdc	100-240Vac; 50Hz – 60Hz
Max output current AC/DC	13A/3A	14A
Lifting height	7M	7M
Lifting Precision	±2mm	±2mm
Load on cable	0.5kg-3kg	0.5kg-3kg
Lifting speed	0-0.5M/S	0-0.5M/S
Control	DMX512 (RDM) over Art-net	DMX512 (RDM) over Art-net
Signal Connection	Wired connection / Wireless connection	Wired connection / Wireless connection
Certifications	BGV C1, CE, ETL, DGUV-17, RoHS	BGV C1, CE, ETL, DGUV-17, RoHS

Apsaras Triangle	APT4
Pixel Pitch	4.8mm
Max Brightness	1500nits
Panel Dimension	1000mm side length
Panel Area	0.433m ²
Panel Pixel Quantity	18539
Panel Weight	4.9kg / 10.80lbs
Power Consumption Max / Average	110W / 55W
BTU Max / Average	375 / 175
Transparency	Solid
Serviceability	Rear
Max. Hanging (panels)	1
LED Configuration	SMD 1921 White
Viewing Angle Horizontal	160°
Viewing Angle Vertical	160°
Scan Ratio	1/15
Refresh Rate	3840Hz
Gray Scale	14bit
Frame Material	Magnesium Alloy + Carbon Fiber
Processing Platform	Brompton
Operational Temp / Humidity	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH
Storage Temp / Humidity	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH
IP Rating	Indoor (IP40)
Certifications	CE, ETL, FCC, RoHS

Notes: The Specifications are for reference, actual values may vary.



www.roevisual.com