

# Specifications

Module	DM2.6	DM3.9
Pixel Pitch	2.60mm	3.91mm
Max. Brightness Calibrated	1,500nits	1,500nits
Panel Dimension	500 x 500 x 80mm 19.7" x 19.7" x 3.2"	500 x 500 x 80mm 19.7" x 19.7" x 3.2"
Panel Resolution (H x V)	192 x 192	128 x 128
Weight per panel	5.76kg; 12.7lbs	5.76kg; 12.7lbs
Power Consumption Max/Average	180W / 90W	150W / 75W
BTU Max/Average	614 / 282	512 / 235
Transparency	Solid	Solid
Max. Curving degree	Concave 10° - Convex 5°	Concave 10° - Convex 5°
Max. Hanging (panels)*1	20	20
Max. Stacking (panels)*2	10	10
LED Configuration	SMD 1515 Black	SMD 2020
Viewing Angle Vertical	140°	140°
Viewing Angle Horizontal	140°	140°
Multiplexing	16	16
Refresh Rate	3840Hz	3840Hz
Gray Scale	16bit	16bit
Frame Material	Magnesium	Magnesium
Operational Temp / Humidity	-20° ~ 45°C, 10-90%RH -4° ~ 113°F, 10-90%RH	-20° ~ 45°C, 10-90%RH -4° ~ 113°F, 10-90%RH
Storage Temp / Humidity	-40° ~ 60°C, 10-90% RH / -40° ~ 140°F, 10-90% RH	-40° ~ 60°C, 10-90% RH / -40° ~ 140°F, 10-90% RH
IP Rating (front/rear)	Indoor	Indoor
Certifications	CE, ETL, TUV	CE, ETL, TUV

\*Notes: The Specifications are for reference, actual values may vary.

1. The max. hanging amount is only valid when the ROE Visual hanging bar and complementary accessories are used and in an indoor situation. No climbing is allowed.
2. The max. stacking amount is only valid when the ROE Visual stacking system and complementary accessories are used, sufficient ballast is applied and in an indoor situation. No climbing is allowed.

## Dimensions



[www.roevisual.com](http://www.roevisual.com)

ROE Visual Co., Ltd. | ROE Visual US, Inc. | ROE Visual Europe BV  
 roe@roevisual.com | roe@roevisual.com | roe@roevisual.com