

# Specifications

Module	SP1.5
Pixel Pitch	1,54mm
Max Brightness Calibrated	800nit
Panel Dimension	494.4 x 278.1 x 86 mm / 19.46" x 10.95" x 3.4"
Panel Resolution (H x V)	320 x 180
Weight Per Panel	4.5kg (9.9lbs)   33.0kg / m <sup>2</sup> (6.7lbs / ft <sup>2</sup> )
Power Consumption Max/Average	100W / 50W
BTU Max/Average	341 / 157
Serviceability	Front
Max. Hanging (panels)	32
Max. Stacking (panels)*1	24
LED Configuration	Mini LED Black
Viewing Angle Vertical	140°
Viewing Angle Horizontal	140°
Multiplexing	20
Refresh Rate	3840Hz
Gray Scale	16bit
Frame Material	Magnesium Alloy
Operational Temp / Humidity	-20°C - 45°C, 10-90%RH / -4°F - 113°F, 10-90%RH
Storage Temp / Humidity	-40°- 60°C, 10-90% RH / -40°-140°F, 10-90% RH
IP Rating	Indoor
Certifications	CE / ETL / FCC Class A / TÜV
<b>Frame</b>	
Frame 2 x 2 Dimension (W x H x D)	988.8 x 556.2 x 80.7 mm / 38.93" x 21.90" x 3.18"
Frame 2 x 2 Weight	11.2 kg (24.6 lbs) / frame / 20.4 kg/m <sup>2</sup> (4.2 lbs / ft <sup>2</sup> )
Frame 1 x 2 Dimension (W x H x D)	494.4 x 556.2 x 80.7 mm / 19.46" x 21.90" x 3.18"
Frame 1 x 2 Weight	6.4 kg (14.1 lbs) / frame / 23.3 kg / m <sup>2</sup> (4.8 lbs / ft <sup>2</sup> )
<b>Combined Panels + Frame</b>	
Weight	52.6 kg / m <sup>2</sup> (10.7 lbs / ft <sup>2</sup> )

\*Notes: The Specifications are for reference, actual values may vary.

1. The max. stacking amount is only valid when the ROE Visual stacking system and complementary accessories are used, sufficient ballast is applied and in an indoor situation. No climbing is allowed.

# Dimensions



[www.roevisual.com](http://www.roevisual.com)

ROE Visual Co., Ltd. | ROE Visual US, Inc. | ROE Visual Europe BV  
 roe@roevisual.com | roe@roevisual.com | roe@roevisual.com