

Specifications

Jasper	Jasper 2.6	Jasper 2.6 half	Jasper 3.9	Jasper 3.9 half
Pixel Pitch	2.60mm	2.60mm	3.91mm	3.91mm
Max Brightness Calibrated	1500nits	1500nits	1400nits	1400nits
Panel Dimension	500mm x 1000mm x 60mm 19.7" x 39.4" x 2.3"	500mm x 500mm x 60mm 19.7" x 19.7" x 2.3"	500mm x 1000mm x 60mm 19.7" x 39.4" x 2.3"	500mm x 500mm x 60mm 19.7" x 19.7" x 2.3"
Panel Resolution (H x V)	192 x 384	192 x 192	128 x 256	128 x 128
Panel Weight	14.15kg; 31.20lbs	7.5kg; 16.53lbs	14.15kg; 31.20lbs	7.5kg; 16.53lbs
Power Consumption Max / Average	340W / 170W	190W / 95W	340W / 170W	160W / 80W
BTU Max / Average	1160 / 533	648 / 298	1160 / 533	546 / 251
Transparency	Solid	Solid	Solid	Solid
Serviceability	Front / Rear	Front / Rear	Front / Rear	Front / Rear
Curving (Concave & Convex)	Concave 15°-Convex 15° (customized)	Concave 10°-Convex 10° (customized)	Concave 15°-Convex 15° (customized)	Concave 10°-Convex 10° (customized)
LED Configuration	SMD 1515 Black	SMD 1515 Black	SMD 2020 Black	SMD 2020 Black
Viewing Angle Horizontal	160°	160°	140°	140°
Viewing Angle Vertical	140°	140°	140°	140°
Scan Ratio	1/16	1/16	1/16	1/16
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz
Gray Scale	14bit	14bit	14bit	14bit
Frame Material	Diecast Aluminum	Diecast Aluminum	Diecast Aluminum	Diecast Aluminum
Installation	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting
Processing Platform	Evision / Brompton / MVR	Evision / Brompton / MVR	Evision / Brompton / MVR	Evision / Brompton / MVR
Operational Temp / Humidity	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH
Storage Temp / Humidity	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH
IP Rating	Indoor	Indoor	Indoor	Indoor
Certifications	CE, ETL, FCC	CE, ETL, FCC	CE, ETL, FCC	CE, ETL, FCC

*Note: The Specifications are for reference, actual values may vary.



www.roevisual.com