

Specifications

Amber	Amber 0.9	Amber 1.2	Amber 1.5	Amber 1.8
Pixel Pitch	0.9375mm	1.25mm	1.5625mm	1.875mm
Max Brightness Calibrated	700nits	800nits	800nits	800nits
Panel Dimension	600 x 337.5 x 55 mm 23.6" x 13.2" x 2.1"	600 x 337.5 x 55 mm 23.6" x 13.2" x 2.1"	600 x 337.5 x 55 mm 23.6" x 13.2" x 2.1"	600 x 337.5 x 55 mm 23.6" x 13.2" x 2.1"
Panel Resolution (H x V)	640 x 360	480 x 270	384 x 216	320 x 180
Panel Weight	8.5kg; 18.7lbs	8.5kg; 18.7lbs	8.5kg; 18.7lbs	8.5kg; 18.7lbs
Power Consumption Max / Average	150W / 75W	170W / 85W	180W / 90W	170W / 85W
BTU Max / Average	515 / 235	580 / 270	615 / 285	580 / 270
Transparency	Solid	Solid	Solid	Solid
Serviceability	Front	Front	Front	Front
LED Configuration	4 in 1 LED	4 in 1 LED	4 in 1 LED	SMD 1010
Viewing Angle Horizontal	160°	160°	160°	160°
Viewing Angle Vertical	140°	140°	140°	140°
Scan Ratio	1/30	1/18	1/18	1/18
Refresh Rate	1920Hz	3840Hz	3840Hz	3840Hz
Gray Scale	16bit	16bit	16bit	16bit
Frame Material	Diecast Aluminum	Diecast Aluminum	Diecast Aluminum	Diecast Aluminum
Installation	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting	Hanging / Stacking / Mounting
Processing Platform	MVR / Brompton	MVR / Brompton	MVR / Brompton	MVR / Brompton
Operational Temp / Humidity	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH
Storage Temp / Humidity	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH
IP Rating	Indoor	Indoor	Indoor	Indoor
Certifications	CE, ETL, FCC	CE, ETL, FCC	CE, ETL, FCC	CE, ETL, FCC

Notes: The specifications are for reference, actual values may vary.



www.roevisual.com

ROE Visual Co., Ltd.
roe@roevisual.com

ROE Visual US, Inc.
roe@roevisual.com

ROE Visual Europe BV
roe@roevisual.com