

Specifications

| Black Marble | BM2-PC Matte |
|---------------------------------|---|
| Pixel Pitch | 2.82mm |
| Max Brightness Calibrated | 800nits |
| Panel Dimension | 609.6mm x 609.6mm x 133mm 24" x 24" x 5.24" 153mm - 193mm (Base Frame) |
| Panel Resolution (H x V) | 216 x 216 |
| Panel Weight | 18.6kg; 41.0lbs |
| Power Consumption Max / Average | 270W / 135W |
| BTU Max / Average | 920 / 420 |
| Transparency | Solid |
| Serviceability | Front |
| LED Configuration | SMD 1515 Black |
| Viewing Angle Horizontal | 140° |
| Scan Ratio | 1/12 |
| Refresh Rate | 3840Hz |
| Gray Scale | 14bit |
| Frame Material | Magnesium Alloy |
| Processing Platform | Brompton / Evision / MVR |
| Operational Temp / Humidity | -20°-45°C, 10-90%RH -4°-113°F, 10-90%RH |
| Storage Temp / Humidity | -40°-60°C, 10-90%RH -40°-140°F, 10-90%RH |
| IP Rating | Outdoor |
| Certifications | CE, ETL, FCC |

Notes: The specifications are for reference, actual values may vary.



www.roevisual.com

Specifications

| Black Marble | BM4 Glass | BM4 Matte |
|---------------------------------|---|---|
| Pixel Pitch | 4.76mm | 4.76mm |
| Max Brightness Calibrated | 800nits | Matte: 2000nits Deep Black Matte: 800nits |
| Panel Dimension | 609.6mm x 609.6mm x 142mm 24" x 24" x 5.6" | 609.6mm x 609.6mm x 135mm 24" x 24" x 5.3" |
| Panel Resolution (H x V) | 128 x 128 | 128 x 128 |
| Panel height incl.frame / feet | 162-202 mm | 155-195 mm |
| Panel Weight | 22.3kg; 49.16lbs | 16.5kg; 36.38lbs |
| Power Consumption Max / Average | 290W / 145W | 290W / 145W |
| BTU Max / Average | 990 / 460 | 990 / 460 |
| Transparency | Solid | Solid |
| Serviceability | Front | Front |
| LED Configuration | SMD 1921 White | SMD 1921 White |
| Viewing Angle Horizontal | 140° | 140° |
| Scan Ratio | 1/8 | 1/8 |
| Refresh Rate | 3840Hz | 3840Hz |
| Gray Scale | 14bit | 14bit |
| Frame Material | Magnesium Alloy | Magnesium Alloy |
| Processing Platform | Brompton / Evision / MVR | Brompton / Evision / MVR |
| Operational Temp / Humidity | -20°~45°C, 10-90%RH -4°~113°F, 10-90%RH | -20°~45°C, 10-90%RH -4°~113°F, 10-90%RH |
| Storage Temp / Humidity | -40°~60°C, 10-90%RH -40°~140°F, 10-90%RH | -40°~60°C, 10-90%RH -40°~140°F, 10-90%RH |
| IP Rating | Outdoor | Outdoor |
| Certifications | CE, ETL, FCC | CE, ETL, FCC |

Notes: The specifications are for reference, actual values may vary.



www.roevisual.com