

Specifications

| Black Marble | BM5-PC Matte | BM5-Glass |
|---------------------------------|---|---|
| Pixel Pitch | 5.76mm | 5.76mm |
| Max Brightness Calibrated | 2000nits | 800nits |
| Panel Dimension | 600mm x 600mm x 103mm 23.6" x 23.6" x 4.1" | 600mm x 600mm x 110mm 23.6" x 23.6" x 4.3" |
| Panel Resolution (H x V) | 104 x 104 | 104 x 104 |
| Panel Weight | 13.5kg; 29.76lbs | 18.3kg; 40.35lbs |
| Power Consumption Max / Average | 270W / 135W | 270W / 135W |
| BTU Max / Average | 920 / 420 | 920 / 420 |
| Transparency | Solid | Solid |
| Serviceability | Front | Front |
| LED Configuration | SMD 1921 White | SMD 1921 White |
| Viewing Angle Horizontal | 140° | 140° |
| Scan Ratio | 1/4 | 1/4 |
| Refresh Rate | 3840Hz | 3840Hz |
| Gray Scale | 14bit | 14bit |
| Frame Material | Magnesium Alloy | Magnesium Alloy |
| Processing Platform | Brompton / Evision | Brompton |
| Operational Temp / Humidity | -20°~ 45°C, 10-90%RH -4°~113°F, 10-90%RH | -20°~ 45°C, 10-90%RH -4°~113°F, 10-90%RH |
| Storage Temp / Humidity | -40°~ 60°C, 10-90%RH -40°~140°F, 10-90%RH | -40°~ 60°C, 10-90%RH -40°~140°F, 10-90%RH |
| IP Rating | Outdoor | Outdoor |
| Certifications | CE, ETL, FCC | CE, ETL |

Notes: The specifications are for reference, actual values may vary.



www.roevisual.com