

Specifications

Black Marble	BM5-PC Matte	BM5-Glass
Pixel Pitch	5.76mm	5.76mm
Max Brightness Calibrated	2000nits	800nits
Panel Dimension	600mm x 600mm x 103mm 23.6" x 23.6" x 4.1"	600mm x 600mm x 103mm 23.6" x 23.6" x 4.1"
Panel Resolution (H x V)	104 x 104	104 x 104
Panel Weight	13.5kg; 29.76lbs	18.3kg; 40.35lbs
Power Consumption Max / Average	270W / 135W	270W / 135W
BTU Max / Average	921 / 424	921 / 424
Transparency	Solid	Solid
Serviceability	Front	Front
LED Configuration	SMD 1921 White	SMD 1921 White
Viewing Angle Horizontal	140°	140°
Scan Ratio	1/4	1/4
Refresh Rate	3840Hz	3840Hz
Gray Scale	16bit	16bit
Frame Material	Magnesium Alloy	Magnesium Alloy
Processing Platform	Brompton / Evision	Brompton
Operational Temp / Humidity	-20°~ 45°C, 10-90%RH -4°~113°F, 10-90%RH	-20°~ 45°C, 10-90%RH -4°~113°F, 10-90%RH
Storage Temp / Humidity	-40°~ 60°C, 10-90%RH -40°~140°F, 10-90%RH	-40°~ 60°C, 10-90%RH -40°~140°F, 10-90%RH
IP Rating	Outdoor	Outdoor
Certifications	CE, ETL, FCC	CE, ETL

Notes: The specifications are for reference, actual values may vary.



www.roevisual.com