

# Specifications

Graphite	GP2.6	GP3.1	GP3.9
Pixel Pitch	2.604mm	3.125mm	3.91mm
Max Brightness Calibrated	1500nits	1500nits	1500nits
Panel Dimension	500 x 1000 x 80 mm 19.7" x 39.4" x 3.1"	500 x 1000 x 80 mm 19.7" x 39.4" x 3.1"	500 x 1000 x 80 mm 19.7" x 39.4" x 3.1"
Panel Resolution (H x V)	192 x 384	160 x 320	128 x 256
Panel Weight	8.5kg; 18.74lbs	8.5kg; 18.74lbs	8.5kg; 18.74lbs
Power Consumption Max / Average	320W / 160W	320W / 160W	320W / 160W
BTU Max / Average	1100 / 500	1100 / 500	1100 / 500
Transparency	Solid	Solid	Solid
Serviceability	Front / Rear	Front / Rear	Front / Rear
Curving (Concave & Convex)	Concave 5° / 0° / Convex 5°	Concave 5° / 0° / Convex 5°	Concave 5° / 0° / Convex 5°
Max. Hanging (panels) *1	12	12	12
Max. Stacking (panels) *2	6	6	6
LED Configuration	SMD 1515 Black	SMD 1515 Black	SMD 1515 Black
Viewing Angle Horizontal	160°	160°	160°
Viewing Angle Vertical	140°	140°	140°
Refresh Rate	3840Hz	3840Hz	3840Hz
Gray Scale	14bit	14bit	14bit
Frame Material	Magnesium Alloy	Magnesium Alloy	Magnesium Alloy
Processing Platform	MVR / Brompton / Evision	MVR / Brompton / Evision	MVR / Brompton / Evision
Operational Temp / Humidity	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH	-20°-45°C, 10-90%RH -4°-113°F, 10-90%RH
Storage Temp / Humidity	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH	-40°-60°C, 10-90%RH -40°-140°F, 10-90%RH
IP Rating	Indoor	Indoor	Indoor
Certifications	CE, ETL, FCC, UKCA	CE, ETL, FCC, UKCA	CE, ETL, FCC, UKCA

\*Notes: The specifications are for reference, actual values may vary.

1. The max. hanging amount is only valid when the ROE Visual hanging bar and complementary accessories are used and in an indoor situation, safety factor is 8. No climbing is allowed.
2. The max. stacking amount is only valid when the ROE Visual stacking system and complementary accessories are used, sufficient ballast is applied and in an indoor situation. No climbing is allowed.



[www.roevisual.com](http://www.roevisual.com)